

Datasheet

Instruction

DNAKE New Door Station provides an integrated security solution. It enables user to open the door by facial recognition with liveness detection, IC & ID card, PIN Code and Bluetooth. It also makes an easy video call with indoor monitor and mobile APP, to achieve a convenient and secure life.

Key Features

- Induction loop for the hearing impaired
- Braille dot for the visually impaired
- Lock Control: 3 (2 Relay out, 1 Electronic lock)
- 120° wide-angle 2MP HD camera with automatic lighting
- Support WDR technology to lighten the dark areas and darken the overexposed parts of the image
- Support 20,000 users, 10,000 faces, and 60,000 cards
- Tamper alarm

Physical

- System: Android 4
- RAM: 512MB
- ROM: 8GB
- Front Panel: Aluminum
- Button: Mechanical
- Power Supply: PoE+ (802.3at) or DC 12V/2A
- Camera: 2MP, CMOS, Dual Cam, WDR
- IR Sensor: Support
- Wiegand Port: Support
- Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive
- Bluetooth: Support BLE 5.0
- TF Card Slot: 1
- Door Entry: Face, IC (13.56MHz) & ID (125kHz) card, PIN code, Bluetooth, NFC, QR Code
- MIFARE Plus SL1/SL3 Card: Support
- Reset Button: 1
- RS485 Port: 1
- Lock Control: 1 Electronic Lock
- Relay Out: 2
- Input: 4
- 12V DC output: 1
- IP / IK Rating: IP66 / IK08
- Installation: Surface Mounting
- Surface Mounting DIM: 295 x 133 x 44.7 mm
- Working Temperature: -40°C to +60°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)

DNAKE D415

(Surface Mounting)



Datasheet

Display

- Display: 4.3-inch IPS LCD
- Resolution: 480 x 272

Networking

- Protocol: SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: 8Ω / 1W

Video

- Video Codec: H.264
- Video Resolution: up to 1920 x 1080
- Max. Image Transfer Rate: 1080p – 25fps
- Light Compensation: LED white light



Datasheet

Instruction

DNAKE New Door Station provides an integrated security solution. It enables user to open the door by facial recognition with liveness detection, IC & ID card, PIN Code and Bluetooth. It also makes an easy video call with indoor monitor and mobile APP, to achieve a convenient and secure life.

Key Features

- Induction loop for the hearing impaired
- Braille dot for the visually impaired
- Lock Control: 3 (2 Relay out, 1 Electronic lock)
- 120° wide-angle 2MP HD camera with automatic lighting
- Support WDR technology to lighten the dark areas and darken the overexposed parts of the image
- Support 20,000 users, 10,000 faces, and 60,000 cards
- Tamper alarm

Physical

- System: Android 4
- RAM: 512MB
- ROM: 8GB
- Front Panel: Aluminum
- Button: Mechanical
- Power Supply: PoE+ (802.3at) or DC 12V/2A
- Camera: 2MP, CMOS, Dual Cam, WDR
- IR Sensor: Support
- Wiegand Port: Support
- Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive
- Bluetooth: Support BLE 5.0
- TF Card Slot: 1
- Door Entry: Face, IC (13.56MHz) & ID (125kHz) card, PIN code, Bluetooth, NFC, QR Code
- MIFARE Plus SL1/SL3 Card: Support
- Reset Button: 1
- RS485 Port: 1
- Lock Control: 1 Electronic Lock
- Relay Out: 2
- Input: 4
- 12V DC output: 1
- IP / IK Rating: IP66 / IK08
- Installation: Surface Mounting
- Flush Mounting DIM: 295 x 133 x 65.5 mm
- Working Temperature: -40°C to +60°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)

DNAKE D415

(Flush Mounting)



Datasheet

Display

- Display: 4.3-inch IPS LCD
- Resolution: 480 x 272

Networking

- Protocol: SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: 8Ω / 1W

Video

- Video Codec: H.264
- Video Resolution: up to 1920 x 1080
- Max. Image Transfer Rate: 1080p – 25fps
- Light Compensation: LED white light

