

Datasheet

Instruction

DNAKE D417 provides an integrated security solution. It enables user to open the door by facial recognition with liveness detection, IC card and PIN Code. It also makes an easy video call with indoor monitor and mobile APP, to achieve a convenient and secure life.

DNAKE D417

(Surface Mounting & Flush Mounting)



Key Features

- 7-inch IPS LCD capacitive touch screen
- 2MP HD camera with automatic lighting
- Support WDR technology to lighten the dark areas and darken the overexposed parts of the image
- Support 20,000 users, 20,000 faces, and 60,000 cards
- Tamper alarm

Physical

- System: Android 4
- RAM: 512 MB
- ROM: 8 GB
- Front Panel: Aluminum
- Power Supply: PoE+ (802.3at) or DC 12V/2A
- Standby Power: 6 W
- Rated Power: 12.5 W
- Camera: 2MP, CMOS, Dual Cam, WDR
- IR Sensor: Support
- Power Out: 12V/100mA (Max.)
- Wiegand Port: Support
- Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive
- Door Entry: Face, IC (13.56MHz) card, PIN code, Bluetooth, NFC, QR code
- Reset Button: 1
- RS485 Port: 1
- Relay Out: 1
- Input: 4
- IP Rating: IP65
- Installation: Surface / Flush Mounting
- Working Temperature: -40°C to +70°C
- Storage Temperature: -10°C to +60°C
- Working Humidity: 20% to 93% (non-condensing)



Datasheet

Display

- Display: 7-inch IPS LCD
- Resolution: 1280 x 800

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: 4Ω / 2W

Video

- Video Codec: H.264
- Video Resolution: up to 1920 x 1080
- Viewing Angle: 81.9°(H) / 51.9°(V) / 89.9°(D)
- Max. Image Transfer Rate: 1080p – 25fps
- Light Compensation: LED white light

Networking

- Protocol: ONVIF, SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

Package Features

- Package Content:
 - DNAKE D417
(Power adapter not included)
 - Flush Mounting Box
 - Screwing Kit
 - Quick Start Guide

